VS Series Order	Rev. Date 7/14/17						
Salesman:	E.	Office Phone:					
INFORMATION IN THIS SECTION IS REQUIRED TO VALIDATE EQUIPMENT WARRANTY							
Bill To Address:	Ship To Address:	End User Address:	End User Type: .com Aero/Auto Consumer Developer Food/Beverage Government Grocery Distribution Grocery Retail Industrial	 Retail Distribution Retail Stores Transportation Pharm/Medical Warehouse Stock Farming Technology Service Entertainment 			
PO#		Requested Ship Date:	Rear Channel Ship Date				

			Industri		Entertainment	
PO#		Requested Ship Date:	R	ear Channe	l Ship Date	
Quantity		Control Box Ship date (if different from leveler ship date)			ate)	
Comments:	Prepaid		Flatbed F	/		
Shipping Instructions:	Collect		Van Requ	uired		
Carrier: Phone	; #:	Third Party				
Leveler Size - REQUIRED		Leveler Capacity - REQUIRED				
$\Box 6' W X 5' L \qquad \Box 6' 6'' W X 5' L$	7'W X 5'L	30,000 lbs. CIR		_ 45,000 lbs		
☐ 6' W X 6'L ☐ 6'6" W X 6'L ☐ 7'W X 6'L		35,000 lbs. CIR] 50,000 lbs	. CIR	
☐ 6' W X 8'L ☐ 6'6" W X 8'L	7'W X 8'L	40,000 lbs. CIR				
New Loading Dock Area		ng Loading Dock Area				
INFORMATION IN THIS SECTION IS REQUIRED TO VALIDATE EQUIPMENT WARRANTY						
Pit Length	Pit Width			Notes:		
Lip Length	I			-		
Pit Depth 10" Standard for 6	6' Long Pit Style	Continuous Pit				
Boards						
☐ 12"		_				
<u> </u>				-		
"" Dock Height						
" Door Size						
" Door Jam Width/Thickness						
" Door Centerlines						
" Building Offset (Panel Sits Fl	ush with Building? Insu	lated Panel Sticks Out From Wa	II. etc)			
	" Building Offset (Panel Sits Flush with Building? Insulated Panel Sticks Out From Wall, etc) Curb Steel / Restraint Steel—REQUIRED					
What Curb Steel Are We Supplying	in Detail?			Notes: a		
🗌 KS4 Pan	Side 🗌	Curb Angle				
Front Curb Angle		Cylinder Imbed Plate				
	Curb Steel for Between rear Ir	nbed				
For Non-Centrapower units, does re require "J" box or hole for electrical	nels rd Imbed Plates					
(Hole is standard unless specified here) Other						
🔲 "J" Box						
Retrofit – Hinge Tube provided on flat plate, to be welded to existing embed channel						
Powerpack Mounting Location Special Coating Requirements						
Platform	anized					
Bollard Deweramp	y Metalized					
□ Wall	☐ Othe	er, describe				
KS4 Pan	Spec	cial Color Paint				
Centrapower						

Electrical – REQUIRED		Notes:			
Electrical Voltage and Phase					
Disconnect Switch (chose only one of the fe					
Light Communication Package (standard: LED	Inside/Incandescent Outside)				
Poweramp supplied power to light package Contractor supplied power to light package	(step down transformer by Systems,Inc.)				
 Overhead door push buttons Poweramp supplied disconnect for th Poweramp supplied fuse protection f Interlock using door operator auxiliary u (provided by door operator manufacturer a Interlock to the door using Poweramp This will only allow leveler to function Poweramp supplied switching device 					
Sequence of Operation/Interlocking - REQ	UIRED	Notes:			
Leveler interlock w/ restraint, Supply sequence engaged/leveler operates. Leveler stored/restraint					
What do we want this interlock to do? Change lights allow leveler to operate when door is fully open do not allow door to operate until leveler is store leveler interlock with communication lights—sup opens/lights change/leveler operates. Levelers lights to change using the stored limit switch (w lights to change using selector switch only (Whether the two opens selector switch only (Whether the two opens) Options requiring dual incoming voltage or stered to change using selector switch only (Whether the two opens) Options requiring dual incoming voltage or stered to change using selector switch only (Whether the two opens) Options requiring dual incoming voltage or stered to change using selector switch only (Whether the two opens) Options requiring dual incoming voltage or stered to change using the source to the dock light the two opens supplied power to the dock light the two opens supplied power to the outlet If we are powering the outlet—what is the minimum Location of outlet on control box? (Outlets will be the two opens) Special locations available upon request at the two opens and the two opens available upon request at the two opens available upon request at the two opens opens available upon request at the two opens opens available upon request at the two opens open					
Bumpers/Keepers— REQUIRED		Notes:			
Bumper Model:	Door Jam Width:				
Maximum height (off drive) of bumper & bracket	Wall offset (set-back/overhang - wall not flus with foundation)—Provide detail	h			
Customer is opening trailer doors into the					
building (*NOTE: target bumpers are strongly recommended)					
Poweramp to supply target bumpers. Target bumper model:					
☐ To be used with 4 th sided seal					
For additional loading dock, construction and safety items go to www.alliedproductsolutions.com.					
Additional Notes:	Net price each: \$				
		Total net price: \$			